

Continental

Refrigerator

FRONT BREATHER WORKTOP REFRIGERATORS



Models Available

- SW27-FB
- SW32-FB
- SW36-FB
- SW48-FB
- SW60-FB
- SW72-FB

Utilizing Environmentally Safe, CFC-free R-134a Refrigerant

Standard Features

- Unique Field Assembled, Bottom Mounted Ventilation System Designed to Allow Cabinets to be Flush Against a Wall or Built into a Counter to Conserve Space
- Modern, State-of-the Art Styling
- Performance Rated Refrigeration System Utilizing Environmentally Safe R-134a Refrigerant
- Unique Airflow Distribution Keeps Product at Uniformly Constant Temperatures
- Easily Serviceable Back Mounted Compressor
- 2" Non-CFC Polyurethane Foam Insulation
- Spring Loaded, Self Closing Door
- Magnetic Snap-In Gasket
- 3½" Casters
- Heavy-Duty, Epoxy-Coated Steel Shelves
- Interior Hanging Thermometer
- Cabinet Construction Consisting of Stainless Steel Front & Top, Aluminum End Panels, Case Back & Interior
- Non-Corrosive, Plasticized Fin Evaporator Coil
- Completely Enclosed, Vented & Removable Case Back
- Automatic, Energy Saving, Non-Electric Condensate Disposal
- 10 ft Cord and Plug Attached

Optional Features & Accessories

• Glass Door Models	• Electric Condensate
• Remote Models-R	• Additional Shelves
• Stainless Steel End Panels-SA Models	• Single Over Shelf
• Stainless Steel Interior & Exterior-SS Models	• Double Over Shelf
	• Door Locks



FRONT BREATHER WORKTOP REFRIGERATORS

SPECIFICATIONS	SW27-FB	SW32-FB	SW36-FB	SW48-FB	SW60-FB	SW72-FB
DIMENSIONAL DATA						
Net Capacity (cu. ft.)	7.4	9.0	10.3	13.4	17.0	20.6
Width, Overall (in.)	27 $\frac{1}{2}$	32	36	48	60	72
Depth, Overall (incl. Hdls.) (in.)	30	30	30	30	30	30
Depth, Body Only (Less Door(s))(in.)	27 $\frac{1}{2}$					
Height (incl. 3 $\frac{5}{8}$ " casters) (in.)	33 $\frac{5}{8}$					
Shelf Area (sq. ft.)	3.5	3.9	4.6	6.8	8.1	10.2
No. of Shelves	1	1	2	2	2	3
No. of Doors	1	1	2	2	2	3
Interior Depth (in.)	20	20	20	20	20	20
Interior Height (in.)	26 $\frac{1}{4}$					
Interior Width (in.)	24 $\frac{1}{2}$	28	32	44	56	68
Condensing Unit Size (H.P.)	1/5	1/5	1/5	1/5	1/4	1/4
Cabinet Electrical	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1
Amps	6.1	6.3	6.3	7.1	7.6	8.6
Fans	2	2	2	3	3	4
Shipping Weight (lbs.)	165	185	225	248	284	318
Shipping Height (in.)	43 $\frac{1}{4}$					
Shipping Length (in.)	35 $\frac{3}{4}$	39	43	55	68 $\frac{1}{4}$	80 $\frac{1}{4}$
Shipping Depth (in.)	37 $\frac{1}{4}$					

